



# T10K Ordering Grid - Room Units

**B27**

Humidity & Combination Temp/Humidity Sensors

Rev. 06/06/07

## Delta Style Room Units

Ordering Information		T10K Transmitter Grid for Delta Style Room Units		
BA/	<b>Sensor Type</b>			
T10K[range]	<b>TEMPERATURE TRANSMITTERS</b> Must include a "range" figure			
	T10K[range]	10K Thermistor, 10,000 Ω @ 25 °C with 4 to 20 mA Output		
	<b>TEMPERATURE TRANSMITTER RANGES</b>			
	Custom temperature transmitter ranges are available. Common ranges are listed below			
	65 TO 80F	18 TO 27C	40 TO 90F	4 TO 32C
	60 TO 80F	15 TO 27C	45 TO 96F	7 TO 35C
	55 TO 85F	13 TO 30C	0 TO 100F	
	50 TO 90F	10 TO 32C		
	<b>Humidity Transmitter</b>			
	-H205	±2% Humidity Transmitter with 0 to 5 V output for temperature & humidity transmitters		
-H220	±2% Humidity Transmitter with 4 to 20 mA* output for temperature & humidity transmitters			
-H305	±3% Humidity Transmitter with 0 to 5 V output for temperature & humidity transmitters			
-H320	±3% Humidity Transmitter with 4 to 20 mA* output for temperature & humidity transmitters			
<b>Enclosure Style</b>				
-R	Delta Style Room Enclosure			
	<b>LCD Display</b> Omit if ordering a unit without display			
D	LCD Display			
	<b>Optional Comm. Jack</b> Mounted in unit's base			
-C35L	3.5 mm Phono Jack w/ Leads Attached			
-C35LT	3.5 mm Phono Style Jack with Leads and			
<b>EXAMPLE</b>				
BA/	T10K[65 TO 80F]	H205	-R D	
Example Part Number: BA/T10K[65 TO 80F]-H205-RD				
<b>Your Part Number:</b>				

\*DC input voltage is required for current output.

Call BAPI if you have questions about the above ordering grid or the configuration of the product you are ordering.